


MONUMENT RECORD

Corner ID: Rich\_Q09

Section Corner

Sections 10, 11, 14, & 15- T09N-R02W, 2nd P.M.  
Richland Township, Monroe County, Indiana



EXISTING SURVEY HISTORY

Include as much detail and history of the corner as known at the time of perpetuation.

ORIGINAL GOVERNMENT SURVEY:

Year Surveyed: 1815 By: William Harris  
Where filed or recorded: Original Notes Page 350  
Original monument: Post  
Bearing Trees or Reference Monuments:

Species	Dia.	Bearing	Distance
Sugar	16"	N 89° W	33 Links
Beech	6"	N 13° E	10 Links

Notes:

SUBSEQUENT CORNER RESTORATION:

Date Surveyed: 2001-2004 By: Steven V. Farkas  
Where filed or recorded: M.C.S.O. Records  
Original monument: Stone  
Bearing Trees or Reference Monuments:

Species	Dia.	Bearing	Distance
Hackberry	14"	N 14° E	15.85'
Box Elder	3"	S 81° E	7.8'
Slippery Elm	17"	S 33° E	134.10'
Black Cherry	12"	N 68° E	87.6'

Notes:

SUBSEQUENT CORNER RESTORATION:

Date Surveyed: 2/27/1860 By: I.S. Buskirk  
Where filed or recorded: Survey Book 2, Page 25  
Original monument: No monument specified  
Bearing Trees or Reference Monuments:

Species	Dia.	Bearing	Distance

Notes:

SUBSEQUENT CORNER RESTORATION:

Date Surveyed: 11/25/1997 By: Kevin P. Enright  
Where filed or recorded: M.C.S.O. Records  
Original monument: Stone w/ "•" in center  
Bearing Trees or Reference Monuments:

Species	Dia.	Bearing	Distance
Hackberry	14"	N 14° E	15.75'
Box Elder	3"	S 81° E	7.60'
Slippery Elm	17"	S 33° E	134.10'

Notes:

**SURVEY EVIDENCE FOUND:** Include evidence found and weighed, search area or areas, search procedure, etc.  
Date of Search: 11/10/21 By: J.R. & K.H. Monument Found: Stone w/ "•" in center BTs or Reference Objects Found: PK nail found in Hackberry Tree, Mag nails found in wood post that previously held survey sign Notes:

**OTHER SURVEY HISTORY:** Include details such as surveyor name, date, recording info, monument description, etc.

PERPETUATION RECORD

**MONUMENT:** Describe monument set or found (Include material type, scribing, distance above/below grade, dimensions.)  
9 inch x 4 inch stone with "•" in center found 5 inches above grade

**OTHER EVIDENCE:** Describe corner location relative to nearby features and how to reach the corner location – note fences, roads, timber cutting lines, mow lines, clearings, plantings, streams, topo changes, etc.  
South of E-W running wire fence in E-W running brushline

**THEORY OF LOCATION:** Describe the theory of location for acceptance of this monument with reference to the recording information for the survey upon which this record is derived. Said recorded survey shall be certified by the same professional surveyor who certifies this document, shall identify and accept this monument, and shall have been recorded within (3) years of Form submittal.  
This stone was found to be referenced by Monroe County Surveyors Steven V. Farkas between 2001—2004 (Tie Sheet not dated) and Kevin P. Enright on November 25th, 1997. This stone was found to be commonly accepted by surveys in the area and was accepted as said corner.

**MONUMENT PRESERVATION:** Describe work done to preserve existing monument. Stone mounds should be placed around monuments when stones are readily available. Paint corner stones but not the scribing. A Monroe County "PROTECT NEARBY SURVEY MARKER" sign shall be attached to a steel post when practicable. Note location and relation of corner to sign.  
Monroe County "PROTECT NEARBY SURVEY MARKER" sign was attached to 12 inch diameter wood post North 30 degrees West 0.75 feet from the stone.

**GEODETIC COORDINATES:** Northing: 1448092.3, Easting: 3086424.4


**BASIS OF GEODETIC COORDINATES:** Describe equipment, date, and personnel used to collect coordinates, datum, epoch, geoid and zone.  
Coordinates shown hereon were obtained from GPS observations utilizing the Indiana Real-Time Network (INCORS). Indiana West Zone, NAD83(2011) Epoch 2010.0000, State Plane Grid Coordinates, US Survey Feet. Geoid model G2012BU7. Datum NAD83\_NO\_TRANS by Jackson Rogers and Kyle Hazelman on November 10th, 2021.

MONUMENT RECORD

Corner ID: Rich\_Q09

Section Corner

Sections 10, 11, 14, & 15- T09N-R02W, 2nd P.M.  
Richland Township, Monroe County, Indiana



**WITNESS MONUMENT TIES:** Describe at least three new BT's and/or witness objects established or work done to preserve existing evidence. The following procedures are provided for guidance. Please utilize professional judgment when choosing witness ties. All ties to BT's should be a magnetic nail and washer (state what kind) set in a hack mark at root crown (less than 12” above ground) perpendicular to center of tree unless otherwise noted. All monuments should be tied to at least three accessories with a minimum of 60° of separation. BTs should be healthy with a minimum DBH of 4”. BT description should include tree species, diameter at 4.5’ above ground, distance of nail above ground, and description of nail location (e.g., SE side of root). Note bearing from monument to the center of the BT, distance to the nail. Other survey monuments that were located in the vicinity and their relation to the monument may also be included.

ID	Bearing	Distance	Description
B	N 30 W	0.75’	12” Dia. Wood Post with sign on SE side
C	N 14 E	15.7’	PK nail found 6” A.G. in E side of 22” Dia. Hackberry tree
D	S 86 E	31.7’	Mag w/ washer set 12” A.G. in S side of 9” Dia. Box Elder tree

Notes:

**MONUMENT LOCATION SKETCH:** Optional: Attach a sketch or aerial image. Monument sketch is not required for reimbursement.

**PHOTO IDENTIFIED:** Photograph close up photo of monument and a vicinity photo of the monument that includes the Monroe County “PROTECT NEARBY SURVEY MARKER” sign. Provide photo orientation and date. Additional photos may be included by clicking the “+” button at the end of the horizontal line.

Photo Date: November 2021



Photo Orientation & Description: Looking North at Q-09



Photo Orientation & Description: Looking West at Q-09

FIELD PERSONNEL:

Field Date: 11/12/21 By: J.R. & K.H. Project #: 21-157 Field Book: , page: Notes:

CERTIFICATION:

Professional Surveyor Name: Eric L. Deckard  
Indiana Professional Surveyor No.: 29900012  
Firm Name: Deckard Land Surveying  
Date: 12/03/21

Signature:

Eric L. Deckard




Seal:

MONUMENT RECORD

Corner ID: Rich\_Q09

Section Corner

Sections 10, 11, 14, & 15- T09N-R02W, 2nd P.M.  
Richland Township, Monroe County, Indiana



OFFICE USE ONLY

NOTICE TO PROCEED AND MONUMENT RECORD FORM ISSUED TO:			
Offeror Name: Eric L. Deckard		Firm Name: Deckard Land Surveying, LLC	
Phone: (812 )961-0235		Email: Ericdeckard1@msn.com	
Corner Classification: Section Corner		Corner Coordinate Status: Perpetuated	
Issue Date: 7/12/22	Form Due Date: 7/21/22		Form Receipt Date: 7/21/2022

COUNTY SURVEYOR APPROVAL:		Seal:
<input checked="" type="checkbox"/> Yes, Signature:	Date: 8/23/22	
<input type="checkbox"/> No, reasons for denial		

SURVEYOR REVIEW BOARD APPROVAL:		Seal:
<input checked="" type="checkbox"/> Yes, Signature:	Date: 8/23/22	
<input type="checkbox"/> No, reasons for denial		